

RG59 BNC Male to Female Assembly Cable 30cm

BNC male to female transmission cable with RG59, 30cm; MOQ 100PCS, custom lengths available.

IMPEDANCE	OUTER DIAMETER
75 ± 3 Ω	**6.1 mm**
MAX. FREQUENCY	
5 ~ 1000 MHz	

BNC-RG59 30cm | 50Ω Coaxial Jumper & Pre-terminated Assemblies

Custom lengths, connectors and pre-assembled jumpers are available. Send us your specification for a quotation.

TECHNICAL DATA

Technical parameters

Source: 2026 Technical Selection Manual

STRUCTURE

Inner conductor	bare copper wire / copper-clad steel wire 0.81 mm
Dielectric	foam PE 3.66 mm
Outer conductor	(shield) laminated aluminum foil + Al-Mg alloy wire braid 3.84 mm
Jacket	PVC or PE 6.10 mm tri-shield aluminum foil + braid + aluminum foil 6.20 mm quad-shield double aluminum foil + double-layer braid 6.73 mm


ELECTRICAL

Characteristic impedance	75 ± 3 Ω
Nominal capacitance	53 pF/m
Velocity of propagation	85 % return loss ≥ 22 dB (0–470 MHz); ≥ 20 dB (470–1000 MHz) shielding attenuation 85 / 85 / 90 / 90 / 90 dB (5 / 50 / 200 / 550 / 800 MHz)
Insulation resistance	≥ 5000 MΩ·km applicable frequency range 5 ~ 1000 MHz

MECHANICAL & ENVIRONMENT

Min. bending radius	≥ 6 × cable OD (fixed installation); ≥ 15 × cable OD (flexible installation)
Operating temperature	PVC −25 ~ +70 °C; PE −40 ~ +85 °C optional shield construction single shield / tri-shield (TRI) / quad-shield (Quad)
Standards	GY/T 135, SJ/T 11138
Applications	CATV drop cable, satellite TV, CCTV and distribution network

ATTENUATION & POWER



Attenuation in dB/100 m at 20 °C, nominal values (±5%).

MHz	dB/100m	MHz	dB/100m
5	2.82	550	19.52
55	6.73	750	22.87
211	12.47	865	24.67
350	15.75	1000	26.64
450	17.72		

Product description

BNC male to female transmission cable with RG59, 30cm; MOQ 100PCS, custom lengths available.