

www.ptlcable.net

RG174 SMA Female to Crimp N Male Assembly Cable

Black straight SMA female to crimp N male assembly with RG174; MOQ 100PCS, custom lengths available.

IMPEDANCE	MAX. FREQUENCY
50±2 Ω	**3000 MHz**

SMA-N RG174 | 50Ω Coaxial Jumper & Pre-terminated Assemblies

Custom lengths, connectors and pre-assembled jumpers are available. Send us your specification for a quotation.

TECHNICAL DATA

Technical parameters

Source: 2026 Technical Selection Manual

STRUCTURE


Inner conductor	nominal diameter / 7*0.16mm
Dielectric	nominal diameter / 1.60mm braid braid coverage / 90% outer jacket nominal diameter / 2.7±0.10mm

MECHANICAL & ENVIRONMENT

Jacket material	PVC / PE
Weight	≈ 8 kg/km

Installation temperature	≥ −20 °C
Standards	IEC 61196-1, MIL-C-17 (equivalent to MIL standard), GB/T 14864
Applications	walkie-talkie, repeater, indoor distribution and equipment-room jumper

ATTENUATION & POWER



Attenuation in dB/100 m at 20 °C, nominal values (±5%).

MHz	dB/100m	MHz	dB/100m
100	28.46	2000	127.28
400	56.92	2500	142.3
900	85.38	3000	155.88
1500	110.23		

Product description

Black straight SMA female to crimp N male assembly with RG174; MOQ 100PCS, custom lengths available.