

RG316D Silver-plated Double-Shielded Cable

50Ω braided coaxial cable with copper conductor and wire braid shield, widely used in radio communication.

IMPEDANCE	OUTER DIAMETER
50±2 Ω	**2.5 mm**
MAX. FREQUENCY	
3000 MHz	

RG316D | 50Ω | 50Ω RG Series Braided Coaxial Cable

Custom lengths, connectors and pre-assembled jumpers are available. Send us your specification for a quotation.

TECHNICAL DATA

Technical parameters

Source: 2026 Technical Selection Manual


STRUCTURE

Inner conductor	silver-plated copper-clad steel wire 7±0.35 × 0.175 2. insulation PTFE 1.52±0.076
Outer conductor	single-layer silver-plated copper braid Nom.1.95
Jacket	FEP 2.5±0.12
Inner conductor	silver-plated copper wire 7/0.17±0.01mm
Dielectric	PTFE 1.52±0.05mm braid silver-plated copper wire 80*0.10mm outer jacket FEP 2.50±0.10 mm

MECHANICAL & ENVIRONMENT

Operating temperature	(°C) -55 to +200 bending radius (mm) 13 ROHS compliant

ATTENUATION & POWER



Attenuation in dB/100 m at 20 °C, nominal values (±5%).

MHz	dB/100m	MHz	dB/100m
100	28.14	2000	125.87
400	56.29	2500	140.72
900	84.43	3000	154.15
1500	109		

Product description

50Ω braided coaxial cable with copper conductor and wire braid shield, widely used in radio communication. Please contact us for detailed specifications.