

HLCTY(R)-50-22 Radiating Cable (7/8")

7/8" radiating leaky cable, 50 ohm, 88% velocity, coupling loss (95%) approx. 78dB at 450MHz, attenuation approx. 3.3dB/100m at 450MHz, min bending radius 250mm for subway and highway tunnels.

IMPEDANCE	OUTER DIAMETER
50 ± 2 Ω	**27.5 mm**

7/8" | 50Ω | 50Ω Leakage Feeder Coaxial Cable

Custom lengths, connectors and pre-assembled jumpers are available. Send us your specification for a quotation.

TECHNICAL DATA

Technical parameters

Source: 2026 Technical Selection Manual

STRUCTURE

Inner conductor	smooth copper tube 9.0 mm
Dielectric	foam PE 23.2 mm
Jacket	black PE / LSZH 27.5 mm

ELECTRICAL

Characteristic impedance	50 ± 2 Ω

Velocity of propagation	88 %
Insulation resistance	> 5000 MΩ·km

MECHANICAL & ENVIRONMENT

Product description

7/8" radiating leaky cable, 50 ohm, 88% velocity, coupling loss (95%) approx. 78dB at 450MHz, attenuation approx. 3.3dB/100m at 450MHz, min bending radius 250mm for subway and highway tunnels.