

HLCTY(R)-50-32 Radiating Cable (1-1/4")

1-1/4" radiating leaky cable, 50 ohm, 88% velocity, coupling loss (95%) approx. 85dB at 450MHz, attenuation approx. 2.1dB/100m at 450MHz, min bending radius 380mm for railway tunnels and mine trunks.

IMPEDANCE	OUTER DIAMETER
50 ± 2 Ω	**37.5 mm**

1-1/4" | 50Ω | 50Ω Leakage Feeder Coaxial Cable

Custom lengths, connectors and pre-assembled jumpers are available. Send us your specification for a quotation.

TECHNICAL DATA

Technical parameters

Source: 2026 Technical Selection Manual

STRUCTURE

Inner conductor	smooth copper tube 13.1 mm
Dielectric	foam PE 32.5 mm
Jacket	black PE / LSZH 37.5 mm

ELECTRICAL

Characteristic impedance	50 ± 2 Ω

Velocity of propagation	88 %
Insulation resistance	> 5000 MΩ·km

MECHANICAL & ENVIRONMENT

Product description

1-1/4" radiating leaky cable, 50 ohm, 88% velocity, coupling loss (95%) approx. 85dB at 450MHz, attenuation approx. 2.1dB/100m at 450MHz, min bending radius 380mm for railway tunnels and mine trunks.